



48A LEVEL 2 - 11.5 kW

CERTIFICATIONS

TUV Rheinland

UL 2231-1, UL 2231-2, UL 2594

AC INPUT

Voltage: 208/240 VAC

Breaker: Rating 60A

Single Connector: 3 Wire (L1, L2 & G)

Double Connector: 5 Wire (L1, L1, L2, L2 & G)

(or)

Voltage: 208/240 VAC

Breaker: Rating 120A

Double Connector: 3 Wire (L1, L2 & G)

AC OUTPUT PER CONNECTOR

11.5 kW at 240VAC

10kW at 208VAC

OPERATING TEMPERATURE

- 25° C to +50° C

- 13° F to +122° F

COMMUNICATIONS

Cellular

PROTOCOL

OCPP 1.6J

DIMENSIONS

71.25" Total Height with Pedestal

36.5" Total Height w/out Pedestal

16" Width Without Connectors

12" Depth

CORD LENGTH

18 feet (standard)

CONNECTORS

SAE J1772 Type 1

ENCLOSURE

Type 3R Aluminum

OPTIONS

Wall Bracket

Pedestal Mount

Branded Door Graphics

GFCI Outlet & Bike Lock Loop

USER INTERFACE

LED Indicators

RFID Card Reader

